

KAIMAN MAXI

WOOD AND GLASS SHELVING SYSTEMS




SYMBOLS AND FINISHES LEGEND

SYMBOLS



NOTE: Printing errors and omissions may exist despite our best efforts to ensure accurancy. We reserve the right to alter specifications without notice.

MATERIALS



AA	Natural	JB	Bright Aluminium	QB	Walnut
AB	White	JC	Aluminium - Chrome	RO	Red
AC	Opal White	JD	Matt Aluminium	UZ	T -Met
AE	White 9010	JE	Satin-finished Aluminium	WA	Bronzed
AK	Champagne	JF	Aluminium - Brass	WI	Burnished
AL	lvory	JG	Aluminium 5	XD	Satin-finished Steel
EA	Black	JL	Aluminium PE 11	YA	Nickel-plated
EB	Glossy Black	JM	Aluminium RAL 9006	YB	Bright Nickel-plated
EC	Matt Black	KA	Chrome	YC	Matt Nickel-plated
EE	Anthracite	KB	Bright Chrome	YD	Satin-finished Nickel-plated
FU	Gunmetal	KC	Matt Chrome	ZA	Zinc alloy
GR	Raw	MA	Brown	ZN	Zinc-plated
HA	Brass-Plated	MB	Light Brown 1	ZQ	Bright Gold
HH	Tropicalized	NN	Metallic Beige	ZY	Titanum
HL	Raw Brass	NO	Beige	ZZ	Clear
IA	Grey	OA	Oak	00	Insignificant finish
IB	Metallic Grey	OZ	Ash		
IF	Middle Grey	PA	Light Ash		
IJ	Light Grey	PZ	Beech		
IL	Grey 20	QA	Maple		

KAIMAN MAXI



KAIMAN MAXI

KAIMAN MAXI: combined wall bracket and shelf support for wood shelf 39 to 73mm thick.

Can be fixed:

- to cement wall with rawlplug Ø 8mm and pan head screw Ø 5x50mm.
- to wood panels with Ø 5mm countersunk head screw only;
- to wood panels 18mm thick with special designed spreading dowel and M6 bolt.

- to plaster board with umbrella fitting Ø 8mm and pan head screw M4x46mm. Useful fixing method for aligning wall brackets and shelf inclination adjustment as

required. Capable of supporting a 25Kg load each (shelf weight included), for a shelf 320mm

Zinc alloy Engineering plastic



25 kg for each shelf support for shelf 320 mm deep




deep.




Recommended fixing countersunk screw type - head Ø 5 mm max.


SHELF LOCKING AND INCLINATION ADJUSTMENT



SOLID AND PLASTERBOARD WALLS



BRACKET ALIGNMENT




It is the responsibility of the customer:

- to ensure that the wall is of a suitable quality to hold the shelf fixing in place.


- to use the proper hardware fittings according to the construction of the wall.


For more specific information, please refer to the WARNINGS section at the end of the catalogue



COMBINATION SHELF LOAD AND SHELF DEPTH

(The figures refer to 1 shelf support)







+ shelf weight = 25 kg MAX for each shelf support




POSITION OF THE RIDGE PLATE






Shelf is clamped between a layer of ridged plastic on both the lower and upper side (coloured parts).



NOTE: KAIMAN MAXI is supplied in carton box including 2 pieces, accessories and fitting guide. Countersunk fixing screws Ø 5x50 and rawlplugs Fischer SX Ø 8x40 to wall are included.







www.italianaferramenta.com