





GLASS SHELF SUPPORTS



# SYMBOLS AND FINISHES LEGEND

### **SYMBOLS**



= SHELF SAFELY LOCKED DURING TRANSPORTATION AND AT HOME.



= ANTI-TURNOVER LOCKING SYSTEM



= NORMS / PATENTS



= PHILLIPS / POZIDRIV



= NEWTON



= PART.NO



= HEXAGONAL SOCKET



= FRICTION



= PCS. PER PACKAGE



= BLADE SLOT



= AUTOMATIC



= COMBI SLOT



= DROP DOWN



= CAPACITY LOADING



= COUNTERSUNK HEAD





= STANDARD HINGE



= WOOD / GLASS THICKNESS



= FLANGE HEAD

= PAN HEAD



= KIMANA HINGE



= DIAMETER

= HOLE DIAMETER



= FLAT HEAD



= FLAP HINGE



= LENGTH



= TRILOBULAR SCREW



= WITH SPRING



= HEIGHT



= SELF-TAPPING SCREW



= WITHOUT SPRING



= RIGHT VERSION



= EURO THREAD



= REVERSED SPRING



= LEFT VERSION



= METRIC THREAD



= PRE-INSERTED SCREW



= FOR ROUND TUBE



= SETTING CODE



= PRE-INSERTED SCREW AND SPREADING BUSH



= FOR OVAL TUBE



= PCS. PER PAD

= CUT ON REQUEST



= WITH BUFFER



= SELF ADHESIVE




= WITH MAGNET




= WITH FLANGE

NOTE: Printing errors and omissions may exist despite our best efforts to ensure accurancy. We reserve the right to alter specifications without notice.

## **MATERIALS**





= OTHER FINISHES AVAILABLE

EPwg	= Water Green Engineering Plastic	SRb	= Black Soft Rubber
			,







## **KRISTAL**

KRISTAL is the new glass shelf support conceived by Italiana Ferramenta Srl, boasting a unique design with its modern and fresh aesthetics.

KRISTAL is a safe shelf support that allows the furniture to be delivered with the shelves pre-mounted. Provided with two layers of soft engineering plastic on both the upper and the lower side, it perfectly locks the shelf, and reduces the risk of damage to the shelf. Locking and unlocking the shelf is absolutely fast and easy with KRISTAL. KRISTAL is available in 2 versions:

- For Glass Shelves 5-6mm thick
- For Glass Shelves up to 8mm thickness

Three different types of installation available:

- Ø 5mm Pin
- With 3,5x12mm countersunk head wood screw
- With M4x16mm countersunk head screw

Zinc alloy and engineering plastic rubber

In accordance with the regulation UNI EN 14749/05 REGISTERED DESIGN















#### INSTALLATION

Assembling with smooth pin


Assembling with alternative fixing options to achieve horizontal connection









#### SHELF INSTALLATION



#### SHELF REMOVAL FOR NEW REPOSITIONING










































## **KRISTAL FIXING ACCESSORIES**











































www.italianaferramenta.com